

SPECIFICATIONS

Current Rating: 1.5 Amps
Insulation Resistance: 1000M Ω Min
Contact Resistance: 20m Ω Max
Withstanding Voltage: AC 500V
Operation Temperature: -40 $^{\circ}$ to +105 $^{\circ}$
Contact Material: Brass
Standard: PA6T
Insulator Material: Polyester(UL 94V-0)
Contact Plating: Gold Flash
Max.Processing Temp: 240 $^{\circ}$ C for 30-60 seconds
(260 $^{\circ}$ C for 5 seconds)

P/N	PIN	DIM.A	DIM.B
FH2.0-01-01PZD-H22	1	0.00	2.00
FH2.0-01-02PZD-H22	2	2.00	4.00
FH2.0-01-03PZD-H22	3	4.00	6.00
FH2.0-01-04PZD-H22	4	6.00	8.00
FH2.0-01-05PZD-H22	5	8.00	10.00
FH2.0-01-06PZD-H22	6	10.00	12.00
FH2.0-01-07PZD-H22	7	12.00	14.00
FH2.0-01-08PZD-H22	8	14.00	16.00
FH2.0-01-09PZD-H22	9	16.00	18.00
.....			
FH2.0-01-40PZD-H22	40	(PIN-1)x2.0	(PIN)x2.0

PART NUMBER DESCRIPTION:

FH2.0-01-NPZD

(D=单排;S=双排)

(Z=直脚;W=弯脚)

(PIN数量;01.....40PIN)

(排针开关)

MANUFACTURE DWG		 东莞市讯普电子科技有限公司 DongGuan XunPu Electronics Co.,Ltd	
UNLESS OTHERWISE SPECIFIED TOLERANCES			TITLE:2.0FH H2.2 1xNPin 180度 U型 PC2.5 6T
			PAR FH2.0-01-NPZD-H22
DECIMALS:	ANGLES:		DWN
X. $\pm$ 0.30	X $^{\circ}$ $\pm$ 5 $^{\circ}$		CHKD
X.X $\pm$ 0.20	X.X $^{\circ}$ $\pm$ 1 $^{\circ}$	CUSTOMER COPY	APVD
X.XX $\pm$ 0.10	X.XX $^{\circ}$ $\pm$ 0.5 $^{\circ}$		SCALE N:A
		SIZE:A4	UNIT:MM
		SHEET:1F1	REV:A

